

One-button SIP-based IP Video Intercom

R26C is a fashionable, SIP-enabled IP video door phone with a RF card reader









# **FEATURES**

# **Physical Features**

Body material: aluminum panel

Camera: 3M pixels, with automatic lighting

RF card reader: 13.56MHz

G-sensor for tamper alarm

Enclosure rating: Ip65

Installation: flush mounting or wall-mounting

## **SIP Features**

• SIP v1 (RFC2543), SIP v2 (RFC3261)

Line: 2 SIP accounts

#### **Interface Features**

1xRJ45 10/100M Mbps Ethernet port

Output relay: 2 relays for door opener

RS485 port

# **Administration Features**

 Auto-provisioning: FTP/TFTP/HTTP/ HTTPS/PnP/DHCP

Configuration management: web-based management or auto provisioning

TR069, SNMP

# **Application Scenarios**

Office door phone with on-site or hosted IP-PBX

Perfect for villa intercom with door access control

Control remote site entry over the internet



## **Audio Features**

• 1 built-in microphone with IP67 rating

2W speaker with IP66 rating

Speech quality: 7 kHz

Echo cancellation, VAD, CNG

## **Video Features**

Resolution: up to 720p

Image transfer rate: 720p@30fps max.

Camera permanently operational

Auto-night mode with LED illumination

Auto white balance

Internal light sensor: image lighting during dark hours

Codec: H.264, MPEG-4 and MJPEG

Support live stream and RTSP

Compliance with ONVIF

