

AKUVOX - R27A

SIP-based IP Video Intercom

R27A is a fashionable, SIP-enabled IP video door phone with a RF card reader and a numeric keypad.









FEATURES

Physical Features

Body material: aluminum panel

Camera: 3M pixels, with automatic lighting

RF card reader: 13.56MHz and 125 kHz

PoE IEEE802.3af

G-sensor for tamper alarm

Support infrared sensor

Enclosure rating: Ip65

Installation: flush mounting or wall-mounting

SIP Features

SIP v1 (RFC2543), SIP v2 (RFC3261)

Line: 2 SIP accounts

Administration Features

 Auto-provisioning: FTP/TFTP/HTTP/ HTTPS/PnP/DHCP

Configuration management: web-based management or auto provisioning

TR069, SNMP

Application Scenarios

Office door phone with on-site or hosted IP-PBX

Perfect for apartment/flat intercom with door access control

Control remote site entry over the internet



Audio Features

1 built-in microphone with IP67 rating

2W speaker with IP66 rating

Speech quality: 7 kHz

Echo cancellation, VAD, CNG

Video Features

Resolution: up to 720p

Image transfer rate: 720p@30fps max.

Camera permanently operational

Auto-night mode with LED illumination

Auto white balance

 Internal light sensor: image lighting during dark hours

Codec: H.264, MPEG-4 and MJPEG

Support live stream and RTSP

Compliance with ONVIF

Interface Features

1xRJ45 10/100M Mbps Ethernet port

Output relay: 3 output relays for door opener

RS485 port, Wiegand port

